

XPON ONU Datasheet

GPON/EPON ONU

3C-ONU-X100W

Date : 2023-08-08

Overview

3C-LINK 3C-ONU-X100W is designed as HGU (Home Gateway Unit) in different FTTH solutions. The carrier-class FTTH application provides different services access.

3C-ONU-X100W is based on mature and stable, cost-effective XPON technology.

3C-ONU-X100W adopts high reliability, easy management, configuration flexibility and good quality of service guarantees to meet the technical performance of EPON Standard of China Telecom CTC3.0 and GPON Standard of ITU-TG.984.X



Feature

- ※ Support EPON/GPON mode and switch mode automatically
- ※ Support Route mode for PPPoE/IPoE/Static IP and Bridge mode
- ※ Support IPv4 and IPv6 Dual mode
- ※ Support 2.4G WIFI 802.11 b/g/n and 2*2 MIMO
- ※ Support LAN IP and DHCP Server configuration
- ※ Support Port Mapping and Loop-Detect Support Firewall function and ACL function Support IGMP Snooping/Proxy multicast feature
- ※ Support TR069 remote configuration and maintenance
- ※ Specialized design for system breakdown prevention to maintain stable system



1GE Ports



Dual Band WIFI



Support EPON/GPON



IPV4/IPV6

Parameter

HARDWARE FEATURES	
Interface	1 SC/UPC Port
	1 10/100/1000Mbps RJ45 LAN Ports
Button	1 Power On/Off Button
	1 Wi-Fi On/Off Button/WPS Button
	1 Reset Button
External Power Supply	12VDC/1A
IEEE Standards	IEEE 802.1, 802.1D, 802.3i, 802.1p, 802.1q, 802.3u, 802.3ab.802.3az
Dimensions (W x D x H)	120*87*32MM
Antenna Type	Omni directional 2T2R
Antenna Gain	2 × 5dBi
XPON Standards	GPON /EPON
Optical Module	Class B+
Optical Wavelength	Transmit at 1310nm
	Receive at 1490nm
Transmission Distance	20Km Max

Bandwidth	Downstream up to 1.25Gbps for EPON. 2.5Gbps for GPON Upstream up to 1.25Gbps
WIRELESS FEATURES	
Wireless Standards	IEEE 802.11b, 802.11g, 802.11n
Wireless Speeds	Up to 300Mbps (dynamic)
Frequency	2.400-2.4835GHz
Transmit Power	<20dBm(EIRP)
Wireless Functions	Enable/Disable Wireless Radio, WDS Bridge, WMM, Wireless Statistics
Wireless Security	64/128-bit WEP,WPA / WPA2,WPA-PSK/ WPA2-PSK encryption, Wireless MAC Filtering
SOFTWARE FEATURES	
Quality of Service	4095 GEM Ports
	Distinguishes priority using Application classifier
	Different Transmission Queues
Security	NAT Firewall, SPI Firewall
	MAC / IP / URL Filtering
	Firewall for Denial of Service(DoS), SYN Flooding, Ping of Death
	IP and MAC Address Binding
Management	OAM
	Web Based Configuration
	Command Line Interface, SSL for TR-069
	Web Based Firmware Upgrade
WAN Connection Type	PPPoE, Dynamic IP, Static IP, Bridge
	Support Multiple WAN connections
DHCP	Server, Client, DHCP Client List,
	Address Reservation, DHCP relay
Port Forwarding	Virtual server, Port Triggering, DMZ, ALG, UPnP
Dynamic DNS	DynDns, NO-IP
VPN Pass-Through	PPTP, L2TP, IPSec Pass-through
Advanced Features	SN, Password, SN+ Password Authentication Mode
	Upstream and Downstream FEC, AES encryption
	Dynamic Bandwidth Allocation(DBA) support NSR/SR
	802.1Q VLAN, Static Routing, RIP v1/v2 (optional); IGMP v1/v2 /v3
OTHERS	
Certification	CE, RoHS
Package Contents	3C-ONU-X100W
	RJ-45 Ethernet Cable
	Quick Installation Guide

	Power Adapter
System Requirements	Microsoft® Windows® 98SE, NT, 2000, XP, Vista™, Windows 7, Windows 8, MAC® OS, NetWare®, UNIX® or Linux.
Environment	Operating Temperature: 0°C~40°C (32°F~104°F)
	Storage Temperature: -40°C~70°C (-40°F~158°F)
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Lights Introduction

Pilot Lamp	Status	Description
WIFI	ON	The WIFI interface is up.
	BLINK	The WIFI interface is sending or/and receiving data (ACT).
	OFF	The WIFI interface is down.
PWR	ON	The device is powered up.
	OFF	The device is powered down.
LOS	BLINK	The device does not receive optical signals or with low signals.
	OFF	The device has received optical signal.
PON	ON	The device has registered to the PON system.
	BLINK	The device is registering the PON system.
	OFF	The device registration is incorrect.
LAN	ON	Port (LAN) is connected properly (LINK).
	BLINK	Port (LAN) is sending or/and receiving data (ACT).
	OFF	Port (LAN) connection exception or not connected.

Application





Specifications are subject to change without notice. It is a registered trademark of 3C-LINK OPTO Co., Ltd. Other brands and product names are trademarks or registered trademarks of their respective holders. No part of the specifications can be reproduced in any form or by any means or used to make any derivative such as translation, transformation, or adaptation without permission from 3C-LINK OPTO Co., Ltd.